



Mineral oil based heavy duty diesel engine oil.

PRODUCT CODE: FAHY

## **EUROFLEET MULTI SAPS 15W/40**

**EUROFLEET MULTI SAPS 15W/40** A high quality part synthetic engine oil that has been designed to meet the lubrication requirements of the modern-day heavy duty diesel engines with strict emission requirements. Incorporating our specialist Adaptive Molecular Technology that has been combined with mid ash technology to optimise the power and efficiency of your vehicle to help maintain peak reliability to ensure maximum performance and emission compliance.

## **BENEFITS:**

- Excellent oxidation stability. Extended service intervals.
- Ideal choice for newer mixed fleet long haul vehicles under Euro V and VI emission standards. Improved soot dispersancy and engine cleanliness.
- Offers improved wear protection.
- Suitable for engines with or without after treatment devices.

Exceeds the following performance criteria ACEA E9/E7 API CK-4/CJ-4 Caterpillar ECF-3 Cummins 20086, 20081 Detroit DDC93K222 Deutz DQC III-10 LA Ford WSS-M2C171-F1 JASO DH-2 Mack EO-S 4.5 MAN M3575 Mercedes-Benz 228.31 MTU Type 2.1 Renault RLD-4, RLD-3 Volvo VDS-4.5, VDS-4/ 4.5

## **TYPICAL ANALYSIS:**

Density @ 15°C	ASTM D4052	0.887
Flash Point (°C)	ASTM D92	210
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	106
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	14.3
Pour Point (°C) ASTM D97 -31	ASTM D97	-31
Total Base Number (mg KOH/g)	ASTM D2896	9.2
Viscosity Index	ASTM D2207	139

