

Universal high performance semi synthetic oil for use in gasolineand diesel engines of passenger car.

FALZOL POWER TRACK 4T

FALZOL POWER TRACK 4T is a universal high performance semi synthetic oil for use in gasoline- and diesel engines of passenger car, lawnmowers and light vans with or without turbocharger. Formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

BENEFITS:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Exceeds the following performance criteria: ACEA A3/B4-08 API SL/CF VW: 501.01 Mercedes 229.1 API: SL/CH API SJ/CD

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m ³	ASTM D4052	865
Kin. Viscosity @40°C	mm²/s	ASTM D7042	90
Kin. Viscosity @100°C	mm²/s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	156
Viscosity CCS @-25°, max.	сР	ASTM D5293	7000
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	6.4
Sulphated Ash	%Wt	ASTM D874	0.95

TYPICAL ANALYSIS:

