



PRODUCT CODE: FAATF3

Universal fluid to be used in automatic transmission.

ATF DEXRON III

Falzol ATF Dexron III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger car, light vans and commercial vehicles. Falzol ATF Dexron III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

BENEFITS:

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF Dexron III exceeds the following performance criteria: DEXRON IIIF/G/H Allison C4 CAT TO-2 MAN 339 Z1/Z2 MAN 339 V1/V2 MB 236.10/236.9/236.7/236.5/236.1 Voith 55.6335 Voith 55.6336 Volvo 97341 Mercon ZF 02F/03D/04D ZF 11A/11B/14B/16L Typical Analysis

TYPICAL ANALYSIS:

| Properties | Unit | Method | Typical Value |
|----------------------------------|--------------------|------------|---------------|
| Color | | | Red |
| Density @15°C | kg/m ³ | ASTM D4052 | 855 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 35 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 7.5 |
| Viscosity Index | | ASTM D2270 | 210 |
| Viscosity Brookfield @-40°, max. | cP | ASTM D5293 | 17500 |
| Flash Point COC | °C | ASTM D92 | 201 |
| Pour Point | °C | ASTM D97 | -51 |