



PRODUCT CODE: FAAFL

Extended Life concentrate
based on Mono Ethylene
Glycol (MEG)

ANTIFREEZE XLL

(BASF GLYSANTIN G30 G33 G34)

Falzol Antifreeze XLL BASF designed corrosion inhibitors to provide protection against frost and corrosion. It needs to be mixed with appropriate amount of water for using as cooling and heat transfer fluid in internal combustion engines. It is free from potentially harmful additives such as nitrites, amines, borate and phosphates and hence it contributes to a safer environment. It is neutral towards gaskets, hoses and provides good resistance against foam.

BENEFITS

- It is extended life coolant based on virtually non depleting synergistic combination of corrosion inhibitors.
- It is having high boiling point which decreases the risk of overheating of Antifreeze.
- It has as improved hard water stability as it does not contain silicates and other mineral salts.
- It is compatible with elastomers used by most of the European OEMs.
- It prevents formation of deposits and scale on the surfaces and also compatible with other MEG based antifreeze.
- It is suitable for mixed fleet
- It is recommended to be used at least 33% dosage of Falzol Antifreeze XLL in 67% water. For enhanced protection, 50% of concentrate in 50% of water is recommended.
- It is recommended for use in cooling systems of all types of liquid cooled **hi-tech** automotive engines where such types of coolants are used. (Please refer OEM manual for recommended coolant) □ It is particularly recommended where high temperature aluminum protection is important.

Meets the requirements of the following European & international standards:
ASTM D 3306 ASTM D 4985 SAE J 1034 BS 6580: 2010 AFNOR NF R15-601
* FFV Heft R443 CUNA NC 956-16 UNE 26361 - 88 JIS K 2234 * NATO S 759
* with the exception of reserve alkalinity

Meets the requirements of the following OEM specifications: Volvo VCS
Coolant Chrysler MS 9176 Cummins 85T8-2 & 90T8-4 Leyland Trucks LTS 22
AF 10 Mack 014GS 17004 MAN 248, 324 (SNF) & B&W D 36 5600 Mercedes
MB 325.3 Renault 41-01-001 VAG TL 774 D/F GM 1899 M, US 6277 M &
OPEL GM QL130100 John Deere H 24 B1 & C1 MTU MTL 5048 Ford ESE
M97B49-A, WSS-M97B44-D & ESD M97B49-A

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Sales@Falzol.ie



JASO



Extended Life concentrate
based on Mono Ethylene
Glycol (MEG)

PRODUCT CODE: FAFAL

Can be used where Glysantin® G12, G12+, G30, G33 or G34 were originally recommended

Warning: Keep all antifreezes out of reach of children. Do not drink antifreeze. If swallowed, induce vomiting and immediately seek medical advice.

TYPICAL ANALYSIS:

Concentration (by volume)	50%
Specific Gravity @ 20°C	1.074
Freeze Protection (°C)*	- 40

*Average of freezing point and pour point.