



High performance fuel conserving oil for gasoline- and diesel engines in passenger cars.

PRODUCT CODE: FASYN

DRIVE 5W-30

FALZOL DRIVE 5W-30 is a high performance fuel conserving oil for gasoline- and diesel engines in passenger cars in light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

FALZOL DRIVE 5W-30 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

BENEFITS:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Longer oil drain interval possible.
- exceeds the following performance criteria:
ACEA A1/B1 API SL ILSAC GF-3 Ford M2C-913A/913B

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15°C	kg/m ³	ASTM D4052	855
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	65
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.3
Viscosity Index		ASTM D2270	175
Viscosity CCS @-30°, max.	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-36
Total Base Number	mgKOH/g	ASTM D2896	8.9
Sulphated Ash	%Wt	ASTM D874	1.15

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Sales@Falzol.ie

