

DRIVE C3 5W-30

FALZOL DRIVE C3 5W-30 A fuel conserving high performance LOW SAPS engine oil based on 100% synthetic technology for gasoline- and diesel engines of passenger cars and light vans specially designed for the latest generation modern vehicles.

FALZOL DRIVE C3 5W-30 is formulated with synthetic base oil in combination with a special selected additive package to ensure the following properties:

BENEFITS:

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for an easy cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties.
- Very good antifoam, anti-wear and anti-corrosion properties.
- LOW SAPS technology, suitable for engines equipped with exhaust gas after treatment like DPF.
- Long oil change interval possible.
- exceeds the following performance criteria: GM Dexos 2 API SN/CF ACEA C3 229.51 BMW LL-04 VW 502.00/505.00 GM-LL-A025/B025

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15°C	kg/m ³	ASTM D4052	854
Kin. Viscosity @40°C	mm²/s	ASTM D7042	68
Kin. Viscosity @100°C	mm²/s	ASTM D7042	11.7
Viscosity Index		ASTM D2270	165
Viscosity CCS @-30°, max.	сР	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7.5
Sulphated Ash	%Wt	ASTM D874	0.80

TYPICAL ANALYSE:





A fuel conserving high performance LOW SAPS engine oil.

PRODUCT CODE: FADRI

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie

