

CHECK YOUR OIL

DRIVE LONG LIFE III 5W-30

FALZOL DRIVE LONG LIFE III 5W-30 is a high performance fuel saving LOW SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed and also suitable for vehicles where MB 229.51 and BMW LL-04 are required.

FALZOL DRIVE LONG LIFE III 5W-30 is formulated with high quality synthetic base stocks in combination with a unique additive technology to achieve the following performance:

BENEFITS:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.
- exceeds the following performance criteria:

ACEA C3 VW 504.00/507.00 MB 229.51 Porsche C30 BMW: LL04

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15°C	kg/m³	ASTM D4052	855
Kin. Viscosity @40°C	mm²/s	ASTM D7042	67
Kin. Viscosity @100°C	mm²/s	ASTM D7042	11.3
Viscosity Index		ASTM D2270	163
Viscosity CCS @-30°, max.	сР	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	8.8
Sulphated Ash	%Wt	ASTM D874	0.7

ACEA **

