

EURO FARM 10W-30

FALZOL EURO FARM 10W-30 A premium quality super universal tractor oil manufactured from a blend of select mineral base oils and specialised additive technology. Suitable to use in four stroke petrol and diesel engines, hydraulic systems and transmissions including equipment with oil immersed wet brakes. It has a very low pour point and a high viscosity index to help ensure minimal wear when cold starting whilst maintaining an effective lubrication film at elevated temperatures to result in a thoroughly universal oil capable of performing in severe operations conditions.

FALZOL EURO FARM 10W-30 is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties.

BENEFITS:

- Good anti-foaming and air release properties.
- Helps reduce wet brake squawk & chatter.
- Powerful anti-corrosion inhibitors which protects all working components.
- Provides excellent anti-wear protection.
- Reduced engine deposits and oil thickening.
- Universal application reduces lubricant stock and prevents misapplication.
- Suitable for: ACEA E3 API (Engine) CG-4 API (Transmission) GL-4 Allison C4 Case MS 1204/1206 Case New Holland MAT 3525 Caterpillar TO-2 Ford M2C134-D, M2C159-B/C John Deere J27, J20C, J20D MAN 271 Massey Ferguson M1135, M1139, M1143, M1144, M1145 New Holland 82009291, 410B Mercedes-Benz 228.1 ZF TE-ML 06B, 06C, 06L, 07B, 07D

TYPICAL ANALYSIS:

Density @ 15°C (kg/m ³)	ASTM D4062	0.868
	//S111 B 1002	01000
		100
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	70
Kinematic viscosity @ 40 C (mm/s-)	ASTH D445	70
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	10.8
Dour Doint (PC)	ASTM D97	-35
Pour Point (°C)	ASTM D97	-33
Viscosity Index	ASTM D2207	144
	/	



Universal mineral based Super Tractor Oil

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie