



A high quality universal semi-synthetic based oil

EURO FARM 10W40

EURO FARM 10W40 for agriculture and earth moving equipment. A high quality universal semi-synthetic based oil developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines.

EURO FARM 10W40 is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF). Formulated on severely hydrocracked base stocks in combination with an unique additive package to reach the following properties.

BENEFITS:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

Exceeds the following performance criteria: Engine Spec API CG-4/CF-4/CE/SF MB 228.1 ACEA E3 JD J20C, J20D, J27 Ford M2C86B, 134D Ford M2C159B Case MS 1204, 6, 7, 9 MF M 1135/1139/1143/1144/1145 CAT TO-2 API GL-4 Allison C4 ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B NH 82009201, 2, Eaton M-2950S Eaton I-280-S Danfoss

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m³	ASTM D4052	861
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	157
Viscosity CCS @-25°, max.	сР	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10.6

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie