

Euro 4 Engines Including Those Fitted with ERG and SCR Systems

EUROFLEET 15W-40

FALZOL EUROFLEET 15W-40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR.

FALZOL EUROFLEET 15W-40 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

BENEFITS:

Product Code: FAHYLDX

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.
- Exceeds the following performance criteria:

PERFORMANCE CRITERIA:

MB-Approval	228.3		
MAN	M 3275		
Volvo	VDS-3		
Renault	RLD-2		
Mack	EO-M		
API	CI-4		
ACEA	E7		
DDC	93K215		
Caterpillar	ECF-1aECF-2		
Global	DHD-1		
JASO	DH-1		
Allison	C4		
MTU	Type 2		
Mack	EO-M+		
Cummins	CES 20077/20078		
DAF	HP2		

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie





Euro 4 Engines Including Those Fitted with ERG and SCR Systems

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density @15°C	kg/m ³	ASTM D4052	880
Kin. Viscosity @40°C	mm²/s	ASTM D7042	101
Kin. Viscosity @100°C	mm²/s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	143
Viscosity CCS @-20°, max.	сР	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10.4
Sulphated Ash	%Wt	ASTM D874	1.5

