



Carefully selected base oils and anti-wear, extreme pressure and anti-corrosion additives

PRODUCT CODE: FASLI68

SLIDE WAY

SLIDE WAY a range of specially designed slideway lubricants. To be efficient, machine tool slideways must be parallel with the machine bed. Any tendency towards irregular oil film pressure and 'slip stick' action must be avoided as this adversely affects the machining operations.

The range of Falzol Slide Way oils have been manufactured from carefully selected base oils and anti-wear, extreme pressure and anti-corrosion additives. They also include special tacky and lubricity additives, which afford good lubricity even at low traverse speeds.

BENEFITS:

- Wide range of viscosities available
- Contains extreme pressure additives for arduous conditions
- Excellent lubricity
- Good corrosion protection

APPLICATION

The Falzol Slide Way range has been specially designed for machine tool slideway applications. They can be recommended for certain combined hydraulic and slideway systems. The lower viscosity grades are suitable for vertical slides and the higher viscosity grades are suited to horizontal slides.

TYPICAL ANALYSIS

Falzol Slide Way	32	46	68	100	150
Product Code	L041	L049	L037	L042	L039
ISO	32	46	68	100	150
Specific Gravity @ 15.6°C	0.873	0.878	0.880	0.889	0.890
Kinematic Viscosity @ 40°C (cSt)	29.85	46.95	69.16	96.84	146.97
Pour point (°C)	-12	-12	-11	-11	-11
Flash point (°C)	215	220	224	226	229
Appearance	Straw	Pale amber	Amber	Amber	Dark amber



Carefully selected base oils and anti-wear, extreme pressure and anti-corrosion additives

PRODUCT CODE: FASLI68