



High quality semi-synthetic  
lubricant

PRODUCT CODE:FA2TIS

## TWO STROKE 2T

Semi Synthetic Two-Stroke 2T Motorcycle Oil is a high quality semi-synthetic lubricant specially developed for high powered 2-stroke air cooled gasoline engines fitted with oil-injection or premix systems.

**FALZOL TWO STROKE 2T** Based on a high quality virgin and synthetic base oils in combination with a special selected additive package to obtain the following properties:

### BENEFITS:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures. Exceeds the following performance criteria: API TC JASO FD ISO-L-EGD

### TYPICAL ANALYSIS:

| Properties            | Unit               | Method     | Typical Value |
|-----------------------|--------------------|------------|---------------|
| Density @15°C         | kg/m <sup>3</sup>  | ASTM D4052 | 872           |
| Kin. Viscosity @40°C  | mm <sup>2</sup> /s | ASTM D445  | 69            |
| Kin. Viscosity @100°C | mm <sup>2</sup> /s | ASTM D445  | 9.5           |
| Viscosity Index       |                    | ASTM D2270 | 123           |
| Flash Point COC       | °C                 | ASTM D92   | 85            |
| Pour Point            | °C                 | ASTM D97   | -33           |
| Total Base Number     | mgKOH/g            | ASTM D2896 | 1.4           |
| Sulphated Ash         | %Wt                | ASTM D78   | 0.14          |