



Universal mineral high grade EP oil for use in heavy duty hydraulic

PRODUCT CODE: FACH68

HYFAST H 68

FALZOL HYFAST H 68 is an universal mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

FALZOL HYFAST H 68 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology.

BENEFITS:

- Excellent stability against oxidation.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- exceeds the following performance criteria:
AFNOR NFE 48-603 ISO 11158 HM DIN 51524/2 HLP Denison HF-2
Cincinnati P-69 Sauer Danfoss 520L0463 Eaton Vickers M-2950-S/I-286

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	68
Density @15°C	kg/m ³	ASTM D4052	882
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	68
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	99
Flash Point COC, min	°C	ASTM D92	180
Pour Point	°C	ASTM D97	-27
Air Release Value @50°C	Mintues	DIN 51381	Pass
Demulsibility @54°C	Minutes	DIN 51599	Pass

Falzol, Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Sales@Falzol.ie

