



For the toughest bearing applications

PRODUCT CODE FASE12.5

## TUF TAC SEMI FLUID 00 and 000 EP

A premium quality grease prepared from refined base oils and lithium hydroxy stearate soap thickener. The grease contains oil soluble EP additives to provide protection against seizure under highly loaded service conditions. The grease also contains additives to inhibit oxidation and rust. This grade of grease is particularly suited for use in industrial equipment and in some automotive gear box applications. The grease is easily pumped over long distances, even at low temperature.

Typical Inspections		
	OOEP	OOOEP
<b>Appearance</b>	<b>Smooth fluid grease</b>	<b>Smooth fluid grease</b>
<b>Colour</b>	<b>Green / Brown</b>	<b>Green/Brown</b>
<b>Penetration (IP50)</b>	<b>400-430</b>	<b>445 - 475</b>
<b>NLGI Classification</b>	<b>00</b>	<b>445 - 475</b>
<b>Timekin OK load (IP 326) Kg</b>	<b>20</b>	<b>000</b>
<b>Operating Temp. Range</b>	<b>-30C to + 110C</b>	<b>20</b>
<b>4 Ball Weld Load KG</b>	<b>315</b>	<b>-30C to +110C</b>
<b>Mean hertz load</b>	<b>58</b>	<b>315</b>
<b>Copper Corrosion (IP112)</b>	<b>1b</b>	<b>58</b>
		<b>1b</b>

